

Serial No. 09/964,564

**IN THE CLAIMS:**

The text of all pending claims are set forth below. Cancelled claims are indicated with claim number and status only. The claims as listed below show added text with underlining and deleted text with ~~strike through~~. The status of each claim is indicated with one of (original), (currently amended), (previously presented), (cancelled), (withdrawn), or (new).

Please AMEND the claims in accordance with the following:

1. (CURRENTLY AMENDED) A method for acceleration and deceleration control for supplying a movement command during cycles of acceleration and deceleration processing to a servo control section controlling axial movement of axes, the method comprising:

determining accelerations by, for each cycle in said acceleration and deceleration processing, determining each acceleration in accordance with a speed obtained at a previous processing cycle, such that a speed-acceleration curve generated by movement commands which are made by the acceleration and deceleration processing will lie along a predetermined speed-acceleration curve, where the predetermined speed-acceleration curve is set for each axis, where said predetermined speed-acceleration curve has different acceleration magnitudes for a given speed magnitude depending on whether an axis is accelerating or decelerating, where the predetermined speed-acceleration curve is predetermined before the generated movement commands, and where for plural speeds of the speed-acceleration curve, corresponding plural accelerations ~~(or, or corresponding plural decelerations)~~ decelerations of the speed-acceleration curve are based on, or equal to, or approximations of corresponding plural accelerations ~~(or, or decelerations, decelerations)~~ of the predetermined speed-acceleration curve of the corresponding axis.

2. (PREVIOUSLY PRESENTED) The method for acceleration and deceleration control according to claim 1, wherein said speed-acceleration curve provides a different acceleration magnitude for each direction of movement.

3. (CANCELLED)

Serial No. 09/964,564

## 4. (CANCELLED)

## 5. (CURRENTLY AMENDED) A numerical control device, comprising:

a memory for storing, for control axes, individual speeds in acceleration and corresponding predetermined restricted accelerations and also storing individual speeds in deceleration and corresponding predetermined restricted decelerations, in the form of a predetermined table;

acceleration-deceleration determination means for determining as to whether or not an acceleration operation should be ~~done~~applied, an operation of a command speed should be ~~done~~applied or a deceleration operation should be ~~done~~applied, for an axis, in a present processing cycle:

speed determination means for determining speeds in the present processing cycle, by using a speed in the present processing cycle as a command speed ~~in the case where~~ said acceleration-deceleration determination means decided that an operation of a command speed be applied, by reading from said memory a predetermined restricted acceleration corresponding to the speed of said axis obtained in the previous processing cycle to determine a speed in the present processing cycle using said predetermined restricted acceleration ~~thus read in the case~~ where said acceleration-deceleration determination means decided that acceleration be applied, or by reading from said memory a restricted deceleration corresponding to the speed of said axis obtained in the previous processing cycle to determine a speed in the present processing cycle using said restricted deceleration ~~thus read in the case where~~ said acceleration-deceleration determination means decided that deceleration be applied; and

output means for finding data on an amount of movement of said axis in the present processing cycle by using the speed found by said speed determination means, and then outputting said data on the amount of movement to a servo control system for said axis.

## 6. (CURRENTLY AMENDED) A method for implementing a movement instruction of an axis, comprising:

providing a speed-to-acceleration mapping that maps speed values to acceleration values based on a direction of movement ~~and a direction of acceleration~~; and

over a sequence of movement cycles for performing the movement instruction during acceleration or deceleration, determining a given movement for a cycle by using the speed-to-

Serial No. 09/964,564

acceleration mapping to map a speed of a previous cycle to an acceleration value and using the acceleration value for the given movement cycle, where accelerations of at least a segment of the speed-to-acceleration mapping coincide with, or approximate, or are based on accelerations of a corresponding segment of an actual physical speed-acceleration mapping of the axis.

7. (CANCELLED)

8. (PREVIOUSLY PRESENTED) A method for acceleration/deceleration control for supplying a movement command which has been subjected to cycles of acceleration/deceleration processing to a servo control section controlling axial movement of axes, the method comprising:

determining accelerations/decelerations for the movement command by, for each cycle in said acceleration/deceleration processing, determining each acceleration/deceleration in accordance with a speed of a previous processing cycle and in accordance with a predetermined speed-acceleration curve, where the predetermined speed-acceleration curve is set for each axis, where the predetermined speed-acceleration curve is predetermined before the determining of the accelerations/decelerations, and where at least a segment of the speed-acceleration curve is equal to, or approximates, or is based on a corresponding segment of an acceleration-restriction curve of the axis being moved.

9. (PREVIOUSLY PRESENTED) A method according to claim 1, wherein the speed acceleration curve is a curve of maximum accelerations for the axis based on a torque output for its motor, based on machine friction, and based on gravity.

10. (CANCELLED).